


See your site in a new light



350° mast rotation

# **L L Compact**

**Manual Legs** 



This compact unit takes its name from its size. At only 2.2 metres high, 1.6 metres wide and 2.3 metres long, seven units can be loaded side by side onto a standard 40 foot trailer or into a 40 foot sea container. Which allows for significant savings in transport cost.

The LEDcompact 2.4K is also quiet enough (64 dba at 7 metres) to be used at events, nighttime road construction and mining. The hydraulically operated tower reaches a height of 8 metres and the tower weighs less than 1.5 tonnes with 350° mast rotation and 180° light bar tilt. This oneman-operated unit is ideal for many applications and is extremely easy to erect and pack away.



- **TRANSPORT 7 UNITS PER 40FT TRAILER**
- USER FRIENDLY
- MINE SITE READY
- SIMPLE ONE PERSON OPERATION
- FULL HYDRAULICS
- AUSTRALIAN MADE **QUALITY BUILT**
- FULLY BUNDED
- **200 HOUR RUNNING** TIME PER TANK
- FUEL CONSUMPTION 1.1LTR PER HOUR
- **3 YEAR WARRANTY ON LED LIGHTS**
- 48 V DC LOW VOLTAGE

# **Light Capacity**

6 x 400 W Briteforce OctaLED 400 lights 2155 square metres @100 lux 360,000 effective lumens

# LIGHT **YOUR SITE TODAY**



















briteforce.com.au



# **BRITEFORCE LEDcompact 2.4K LIGHTING TOWER SPECIFICATIONS**

### **MAST SYSTEM**

Max Mast Height 8 metres

Raise Hydraulic (One ram)

Light Bar Tilt Electric 180° (12 V DC)

Mast Rotation Manual 350°

Hydraulic System 12 V DC power unit

Wind Load Certification 100 km/h

### **DIMENSIONS**

Overall Height 2.2 metres Overall Width 1.6 metres Overall Length 2.3 metres Dry Weight 1240 kg

Wet Weight 1420 kg

Max towing Speed 100 km/h

Wind load Certified 100 km/h

### **ELECTRICAL CONTROLS**

Auto Start Self-start ready

Auto Stop Real time adjustable timer

Boom Operation Electric over hydraulic

Switch Operated 12 V DC power

Engine Protection Fail safe (oil, temp, low coolant) No Load Safety Start Up Prevents starting and stopping under load

Emergency Stop 12 V DC power pnit

Main Circuit Breaker 100 A

### **ENGINE**

Yanmar 3TNV70 3 cylinder

Engine Speed 1500 rpm

Engine Power 6.1 kW

Hydraulic Oil Tank 1.5 litres

Fuel Tank 220 litres

Fuel Consumption 1.1 litres per hour

### ALTERNATOR / GENERATOR / NSM (PMG)

Bearingless Brushless

Output Voltage 48 V DC output

Output Amps 63 A

## BRITEFORCE LIGHTS

LED 48 V DC light

Wattage 400 W per light

2155 square metres 6 x Light Coverage @100 lux 360,000 effective lumens

Warranty 3 years on LED lights

# **CHASSIS**

Base Heavy duty RHS construction

Suspension Heavy duty off road

Axle Heavy duty off road

Brakes Mechanical cable drum

Hand Brake Mechanical cable

Wheels R16 R0H off road L/C 6 stud

Tie Down Points 4

Manual Wind Down Stabilisers 4 legs

### LIFTING


Two Point Certified

Fork Lift Pockets Both sides and rear

### OPTIONS

o. none	
Rubber battery cover	75mm ring hitch
Cat style jump start recepticals	1500 hour service kit (oil,fuel and air)
4.5kg dry chemical fire extinguisher with quick release bracket	Custom colour choice
Exhaust system blanket	Day/night auto start stop sensor
Locking gas stays	Wheel nut indicators
Electric fuel sender with low fuel warning display	Internal work light
Wheel chocks & S/S brackets x 2	Extended light Bar 9.6 metres
High vis asset numbers & strips	







See your site in a new light

3 Meliador Way, Midvale WA 6056 e sales@briteforce.com.au

1300 003 533 briteforce.com.au

